

nayo P 4K

NAYO P 4K

neva
lux

Product code 220175

- Focused light for conference rooms, counters, workplaces
- High luminaire efficiency with 130 lm/W
- Ideal for narrow beam illumination
- Direct and indirect light distribution
- Deeply recessed, absolutely glare-free optics (UGR < 10)
- Link technology for seamless extension of luminaire with plugs
- Dimmable DALI, LiveLink compatible
- Housing Aluminium RAL9016, white

neva
lux

1190 x 160 x 30 mm



nayo P 4K

NAYO P 4K

Product code **220175**

Technical Data

DIMENSIONS

Dimensions L x W x H	1190 x 160 x 30 mm
Suspension length	1500 mm

ELECTRICAL

Mains connection	200...240 V / 50 – 60 Hz
Power	60 W
Replaceable driver	Yes
Type of wiring	Through wiring included

SENSOR TECHNOLOGY

With motion detector	No
With light sensor	No

LIGHTING TECHNOLOGY

Colour temperature	4000 K
LED colour deviation	SDCM3
Colour rendering index	80-89

Illuminant	LED
Luminous flux	6700 lm (Down 3400, Up 3300)

Beam angle	Down 50°, Up 115°
Luminaire luminous efficacy	112 lm/W
Glare value	UGR < 10

LIFETIME

LED lifespan (25 °C)	50000 h
----------------------	---------

SETTINGS

DALI dimming	Yes
With emergency light	No
Suitable for light band configuration	Yes
Direct/indirect ratio separately controllable	No

Constant light output control	Yes
-------------------------------	-----

HOUSING & MATERIAL

Protection class (IP)	IP20
Protection class	I
Ambient temperature	-20...45 °C
Housing material	Aluminum
Cover material	Darklight Optics
Mounting type	Ceiling pendant
Colour	white

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty **5 years**

CERTIFICATES & EPREL

EPREL energy efficiency class

nayo P 4K

NAYO P 4K

Product code **220175**

Accessories

ORDERING INFORMATION

Art.-Nr. 220175

Typ nayo P 4K

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss