

nyota connect C400 4K 120

NYOTA CONNECT C400 4K 120

neva
lux

Product code 221515

- The intelligent high bay luminaire nyota from nevalux makes the refurbishment of large industrial, logistics and exhibition halls child's play. Old spotlights can easily be replaced by new luminaires. This creates the most modern lighting management system of today. During commissioning, groups are formed, follow-up times are defined and the brightness for constant light control is set. Energy savings of more than 80% compared to old technologies are the order of the day. The IP65 jet water protection in combination with the IK09 shock resistance rating make this luminaire almost indestructible.

neva
lux

400 x 166 mm



nyota connect C400 4K 120

Product code 221515

NYOTA CONNECT C400 4K 120

Technical Data

DIMENSIONS		CONNECTIVITY		With program-controlled lighting control	Yes
Dimensions Ø x H	400 x 166 mm	With radio network control			
ELECTRICAL		LIGHTING TECHNOLOGY		HOUSING & MATERIAL	
Mains connection	200...240 V / 50 – 60 Hz	Colour temperature	4000 K	Impact resistance	IK09
Power	200 W	LED colour deviation	SDCM3	Protection class (IP)	IP65
Replaceable driver	Yes	Colour rendering index	80-89	Protection class	I
Maximum number of luminaires per circuit breaker	C10: 5x, C13: 6x, C16: 8x, C25: 12x, B10: 3x, B13: 4x, B16: 5x, B25: 7x	Illuminant	LED	Ambient temperature	-20...50 °C
SENSOR TECHNOLOGY		Luminous flux	32000 lm	Housing material	Steel
Sensor technology	passive infrared	Beam angle	120°	Cover material	Diffusor opal
With motion detector	Yes	Luminaire luminous efficacy	160 lm/W	Mounting type	Ceiling / Wall / Pendant
Detection angle	360 °	Glare value	UGR < 30	Colour	black
		LIFETIME		SCOPE OF DELIVERY & WARRANTY	
Radial range	4 x 4 m (16 m²)	LED lifespan (25 °C)	50000 h	Manufacturer warranty	5 years
Tangential range	6 x 6 m (36 m²)	SETTINGS		CERTIFICATES & EPREL	
Mounting height	< 10 m	DALI dimming	Yes	EPREL energy efficiency class	C
Presence range	4 x 4 m (16 m²)	With emergency light	No		
With light sensor	Yes				

nyota connect C400 4K 120

Product code 221515

NYOTA CONNECT C400 4K 120

Illustrations

MOUNTING HEIGHT

< 10 m BEREICH

nyota connect C400 4K 120

Product code 221515

NYOTA CONNECT C400 4K 120

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

221515

Typ

nyota connect C400 4K 120

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss