

nefera C120 4K

NEFERA C / P / W

neva
lux

Product code **220173**

- For universal use in office and school lighting, Traffic zones etc.
- Flat design and completely homogeneous illumination
- High quality finish
- Direct and indirect light distribution
- Very good glare control values (UGR<17)
- Dimmable DALI
- Housing Aluminium white

neva
lux

1200 x 260 x 30 mm



nefera C120 4K

NEFERA C / P / W

Product code 220173

Technical Data

DIMENSIONS				HOUSING & MATERIAL	
Dimensions L x W x H	1200 x 260 x 30 mm	LED colour deviation	SDCM3	Protection class (IP)	IP20
ELECTRICAL		Colour rendering index	80-89	Protection class	I
Mains connection	200...240 V / 50 – 60 Hz	Illuminant	LED	Ambient temperature	-20...45 °C
Power	60 W	Luminous flux	5400 lm (Down 4200, Up 1200)	Housing material	Aluminum
Replaceable driver	Yes	Beam angle	Down 90°, Up 110°	Cover material	Microprismatic acrylic glass
Type of wiring	Suitable for through wiring	Luminaire luminous efficacy	90 lm/W	Mounting type	Ceiling surface-mounted
LED rated current	1500 mA	Glare value	UGR < 19	Colour	white
SENSOR TECHNOLOGY		LIFETIME		SCOPE OF DELIVERY & WARRANTY	
With motion detector	No	LED lifespan (25 °C)	50000 h	Manufacturer warranty	5 years
With light sensor	No	SETTINGS		CERTIFICATES & EPREL	
LIGHTING TECHNOLOGY		DALI dimming	Yes	EPREL energy efficiency class	F
Colour temperature	4000 K	With emergency light	No		

nefera C120 4K

Product code **220173**

NEFERA C / P / W

Accessories

ORDERING INFORMATION

Art.-Nr. 220173

Typ **nefera C120 4K**

**neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss