

nyota C400 4K 90

NYOTA CONNECT

neva
lux

Product code **221585**

- Intelligent high bay luminaire for inspiring lighting solutions in industry
- Available as intelligent Connect or conventional DALI variant
- Connect variant with powerful IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- 32'000 lumens at 160 lm/W
- 3 different optics to choose from
- Robust, high-quality construction IP65 and IK09

neva
lux

400 x 137 mm



nyota C400 4K 90

Product code 221585

NYOTA CONNECT

Technical Data

DIMENSIONS				HOUSING & MATERIAL	
Dimensions Ø × H	400 x 137 mm	LED colour deviation	SDCM3	Impact resistance	IK09
ELECTRICAL		Colour rendering index	80-89	Protection class (IP)	IP65
Mains connection	200...240 V / 50 – 60 Hz	Illuminant	LED	Protection class	I
Power	200 W	Luminous flux	32000 lm	Ambient temperature	-20...50 °C
Replaceable driver	Yes	Beam angle	90°	Housing material	Steel
Maximum number of luminaires per circuit breaker	C10: 5x, C13: 6x, C16: 8x, C25: 12x, B10: 3x, B13: 4x, B16: 5x, B25: 7x	Luminaire luminous efficacy	160 lm/W	Cover material	Lens transparent
SENSOR TECHNOLOGY		Glare value	UGR < 22	Mounting type	Ceiling / Wall / Pendant
With motion detector	No	LIFETIME		Colour	black
With light sensor	No	LED lifespan (25 °C)	50000 h	SCOPE OF DELIVERY & WARRANTY	
LIGHTING TECHNOLOGY		SETTINGS		Manufacturer warranty	5 years
Colour temperature	4000 K	DALI dimming	Yes	CERTIFICATES & EPREL	
		With emergency light	No	EPREL energy efficiency class	C

nyota C400 4K 90

NYOTA CONNECT

Product code **221585**

Accessories

ORDERING INFORMATION

Art.-Nr. 221585

Typ nyota C400 4K 90

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss